

# HP ProCurve 8212zl Switch

## Safety and Regulatory Information



### WARNING

**Do not wall mount the 8212zl switch**

Applicable Products	HP ProCurve 8212zl Switch (J8715A)
Environmental Operating Temperature:	0°C to 45°C (32°F to 113°F)
Relative humidity:	15% to 80% at 40°C (104°F) (non-condensing)
Non-Operating Temperature:	-40°C to 70°C (-40°F to 158°F)
Non-Operating Relative humidity:	20% to 90% at 70°C (158°F)
Maximum Operating Altitude:	3.1 km (10,000 ft)
Non-Operating Altitude:	4.6 km (15,000 ft)
Acoustics:	Geräuschemission LpA=47.8 dB am fiktiven Arbeitsplatz nach DIN 45635 T.19 Noise Emission LpA=47.8 dB at virtual workspace according to DIN 45635 T.19
Safety:	EN55024, CSA 22.2 No. 60950, UL 60950, IEC 60950

## HP ProCurve Power Supplies

Electrical	J8712A		J8713A	J9306A	
	100-127 volts	200-240 volts	200-240 volts	110-127 volts	200-240 volts
<b>AC voltage:</b>	100-127 volts	200-240 volts	200-240 volts	110-127 volts	200-240 volts
<b>Maximum current:</b>	12 A max	5 A max	10 A max	13 A max	10 A max
<b>Frequency range:</b>	50/60 Hz	50/60 Hz	50/60 Hz	50/60 Hz	50/60 Hz
<b>PoE output wattage:</b>	273 W	273 W	900 W	300 W	900 W

### Power cord, one of the following:

J8712A Power Supply		J8713A Power Supply	
Region	Cable	Region	Cable
Australia/New Zealand	8121-0857	Australia/New Zealand	8121-0871
China	8121-1034	China	8121-0924
Continental Europe	8120-5336	Continental Europe	8120-6899
Denmark	8120-5340	Denmark	8120-6897
Japan	8120-5342	Japan	8120-6903
Switzerland	8120-5339	Switzerland	8120-6897
United Kingdom/Hong Kong/Singapore	8120-5334	United Kingdom/Hong Kong/Singapore	8120-6898
United States/Canada/Mexico	8121-0973	United States/Canada/Mexico	8120-6903
South Africa	8120-5341	South Africa	8121-0915
Taiwan	8121-0941	Taiwan	8120-6903

J9306A Power Supply		Region	Cable
Region	Cable	Region	Cable
Australia/New Zealand	8121-0857	Israel	8121-1009
China	8121-1034	Thailand	8121-0671
Continental Europe	8120-5336	Taiwan (110V operation)	8121-0967
Denmark	8120-5340	Taiwan (NEMA L6-20, 220V)	8121-0941
Japan (NEMA L6-20, 200V)	8121-0941		
Switzerland	8120-5339		
United Kingdom/Hong Kong/Singapore	8120-5334		
U.S./Canada/Mexico (NEMA5-15, 120V)	8121-0973		
U.S./Canada/Mexico (NEMA L6-20, 240V)	8121-0941		
South Africa/India	8120-5341		

## Note

When selecting a pluggable transceiver, considering safety, make sure it can function at a temperature that is the same or greater than the recommended maximum operational temperature of the product.

## Battery Statements:

### ATTENTION

Il y a danger d'explosion s'il y a remplacement incorrect de la batterie.

Remplacer uniquement avec une batterie du même type ou d'un type équivalent recommandé par le constructeur.

Mettre au rebut les batteries usagées conformément aux instructions du fabricant.

### ATTENTION



The battery supplied with this product may contain perchlorate material. Special handling may apply in California and certain other states. See [www.dtsc.ca.gov/hazardouswaste/perchlorate](http://www.dtsc.ca.gov/hazardouswaste/perchlorate) Web site for more information.

## Caution

Risk of explosion if battery is replaced by an incorrect type. Dispose of used batteries according to the instructions.

### European Community

### China Regulatory

		<b>DECLARATION OF CONFORMITY</b> according to ISO/IEC 17050-1 and EN 17050-1	
		<b>DoC #:</b> RSVLC-0503-07272009	
<b>Supplier's Name:</b>	Hewlett-Packard Company		
<b>Manufacturer's Address:</b>	8000 Foothills Blvd., Roseville, CA 95747 U.S.A.		
<b>declares, that the product</b>			
<b>Product Name<sup>2</sup>:</b>	HP ProCurve 5406zl Switch, HP ProCurve 5412zl Switch HP ProCurve 8206zl Switch, HP ProCurve 8212zl Switch		
<b>Product Number(s):</b>	J8697A, J8698A, J8699A, J8700A, J8715A, J8715B, J9091A, J9447A, J9448A, J9477A		
<b>Regulatory Model No<sup>1</sup>:</b>	RSVLC-0503		
<b>Options:</b>	J8736A, J8702A, J8705A, J8706A, J8707A, J8708A, J8712A, J8713A, J8714A, J4858B, J4858C, J4859B, J4859C, J4860B, J4850C, J8177B, J8177C, J8436A, J8437A, J8438A, J8439A, J8440A, J8714A, J9051A, J9052A, J9092A*, J9093A*, J9095A*, J9099B, J9100B, J9142B, J9143B, J9144A, J9154A, J9155A, RSVLC-0503-A, J9306A, J9307A, J9308A, J9309A, J9478A, J9475A, J9370A, J9289A		
	* For use with ProCurve Switch Series 8200 only		
<b>conforms to the following Product Specifications and Regulations:</b>			
<b>EMC:</b> Class A EN 55022: 2006 EN 55024:1998 +A1(2001)+A2 (2003) EN 61000-3-2:2006 EN 61000-3-3:1995 +A1(2001) +A2(2005) FCC CFR47 Part 15			
<b>Safety:</b> EN 60950-1:2001 +A11:2004 IEC 60950-1: 2001 EN 60825-1:1994 +A1+A2 / IEC 60825-1:1993 +A2 Class 1			
<b>Supplementary Information:</b> The device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) this device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation. The product herewith complies with the requirements of the Low Voltage Directive 2006/95/EC, the EMC Directive 2004/108/EC and carries the CE marking accordingly.			
<b>Additional Information:</b> 1) This product is assigned a Regulatory Model Number which stays with the regulatory aspects of the design. The Regulatory Model Number is the main product identifier in the regulatory documentation and test reports, this number should not be confused with the marketing name or the product numbers. 2) This product was tested with HP branded products only.			
Roseville, 27 July, 2009		 Michael E. Avery, Regulatory Eng. Manager	
<b>Local contact for regulatory information:</b> EMEA: Hewlett-Packard GmbH, HQ-TRE, Herrenberger Straße 140, D-71034 Böblingen, Germany U.S.: Hewlett-Packard, 3000 Hanover St., Palo Alto, CA 94304, U.S.A. 650-857-1501			

### 有毒、有害物质/元素及其含量表

依照中国  
《电子信息产品污染控制管理办法》

部件名称	有毒、有害物质和元素					
	铅 (Pb)	汞 (Hg)	镉 (Cd)	六价铬 (Cr(VI))	多溴联苯 (PBB)	多溴代二苯醚 (PBDE)
机箱/隔板/其它金属和塑料部件	0	0	0	0	0	0
印刷电路组件 (PCA)	X	0	0	0	0	0
天线	X	0	0	0	0	0
电缆/电线	X	0	0	0	0	0
电池	0	0	0	0	0	0
风扇/风扇盘	0	0	0	0	0	0
电源/电源适配器	X	0	0	0	0	0
安装支架/其它附件	0	0	0	0	0	0
CF卡	0	0	0	0	0	0

0:表示此部件使用的所有同类材料中此种有毒或有害物质的含量均低于 SJ/T11363-2006 规定的限制要求。  
X:表示此部件使用的至少一种同类材料中,此种有毒或有害物质的含量高于 SJ/T11363-2006 规定的限制要求。

注:所引用的环保使用期限标记根据产品的正常操作使用条件(如温度和湿度)确定。



除非另有标明,此电子信息产品污染控制标记适用于所有 ProCurve Networking by HP 产品。

This information is required by the People's Republic of China as per their legislation titled "Management Methods for Controlling Pollution by Electronic Information Products".

